

LOBADUR[®] WS EasyFill Plus



Product description

Waterborne, fast drying binder based on acrylate for the production of wood putty.

Range of Use:

For filling joints and repairing minor defects in glued down parquet and hardwood floors; can be used with any type of wood.

Excessively wide joints contaminated with dirt and dust in older wood floors, joints in wood flooring installed over flexible underlayments, as well as nailed or screwed wood floors are generally not filled because at least some of the dried filler would eventually come loose. Produces a wood filler that dries with good filling properties and good adhesion.

Features

- low consumption
- fast drying
- no odor nuisance
- easy application
- suitable for all types of wood

Technical Data

Article No.	11038	Coverage	On newly laid parquet with small joints approx.. 500-800 sqft/gal
Package Size	1 gallon	Application Tool	LOBATOOL stainless trowel
Packaging	Case: 4 x 1 US gallon plastic bottle Pallet: 200 x 1 US gallon plastic bottle	Drying Time	Sanding after 20 to 40 minutes, depending on the width of the joint.
Solids	20 ± 1%	Earliest possible application of waterborne LOBADUR [®] systems & LOBASOL [®] oil systems after 1 h	
US Regulatory VOC	< 165 grams per liter	Thinner	The product is ready-to-use and cannot be diluted!
Storage	41°F to 77°F. KEEP FROM FREEZING.		
Shelf life	12 months in unopened original containers.		

LOBADUR[®] WS EasyFill Plus

Directions

- For professional Use only!
- BEFORE USING, READ AND UNDERSTAND ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-Wakol Technical Service at 1-800.230.6456.
- Sand and prepare floors according to NWFA instructions.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F. Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Mix WS EasyFillPlus with very fine wood dust from sanding into a smooth mass
- The finer the dusting sand, the easier it will be to trowel- fill the mass and there will also be a better adhesion in the joints
- Trowel-fill the complete floor before the final cut. Repeat procedure on larger joints or damages after drying.
- Thoroughly peel all remains off of surface
- Completely sand off all putty from area (final cut)

Recommended Procedure for wood floors:

1. Sand with coarse and medium sanding paper (e.g. grade 36 , grade 60)
2. Trowel-fill with putty
3. Drying 20-40 min.
4. Final Cut (e.g. grade 100 / 120)
5. Surface treatment

Possible Surface Treatment with:

Any waterborne LOBADUR[®] finish system or any LOBASOL[®] oil system, without limitation.

Sanding:

Completely sand off all putty from area (final cut)

Cure Time:

The stated drying and cure times are based on ideal conditions (68°F, 65% rH) at the recommended application rates. Recommended conditions are 50°F-77°F/40-75%rH). Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. The floor can be lightly used 24 hours after application, but is still susceptible to scuffing or marring at this time. Full curing is achieved after 5 days. Do not use safety covers on floor, do not replace carpets or rugs and also do not clean floors with a damp cloth before the final hardness has been reached.

Screen and Recoat:

Do NOT use LOBADUR[®] WS EasyFill Plus on Factory Finished or Manually Finished Floors. Only for the application directly on the wood. LOBADUR[®] WS EasyFill Plus must be overcoated with LOBADUR waterbased finishes or LOBASOL oil systems.

Compatibility:

When this product is used in combination with other LOBA products also the Technical Information of these products has to be followed. Always prepare test areas to determine suitability of other products than LOBA.

Clean-up:

Use water to clean tools immediately after use. Do not dispose finish left overs with household garbage; unused product must not be poured into the sewage system, but must be brought to the chemical waste disposal according to local, state, and federal regulations after complete curing.

Technical Information



LOBADUR[®] WS EasyFill Plus

Maintenance:
Floor Care: Clean floor with wet cloth or mop only after full cure is reached. Do not clean with water or detergent during the first week. After one week we recommend the use of Hardwood Floor Cleaner. Put walk-off mats at all entrance doorways to minimize dirt and grit. Sweep or vacuum daily and damp-wipe with Hardwood Floor Cleaner. Use felt pads under furniture legs and appliances. Place furniture and other heavy appliances carefully.
Plasticizer containing materials: Plasticizer containing materials e.g. carpet padding, furniture padding, chair rolls, elastic glues etc. could lead to softening and discoloration of the finish. Visit www.loba-wakol.com for additional information and instruction about floor care and maintenance.
Safety Precautions:
Even when working with low-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Make sure working areas are ventilated sufficiently. Clean left-overs off of hands. Change soiled clothes. Ventilate working rooms during working and drying time avoiding draft.
First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If breathing is difficult or other respiratory complaints, get medical attention. In case of contact, immediately flush eyes or skin with plenty of water. Do not use solvents or thinners. Remove contaminated clothing or shoes. For eye contact, rinse opened eye for several minutes under running water. Call a physician if irritation occurs.
WARNING! If you scrape, sand or remove old paint from wooden floors, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead .
Special Information:
The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.
The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical information is also available by visiting our website www.loba-wakol.com . You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the Technical Information concerning those products.