

LOBADUR® Fugenkittlösung

Product description

Solvent Based Bonding Agent for the Production of Wood **Putty**

Low-emission alternative products

LOBADUR® waterbased filler

Range of Use:

To fill in joints and smaller damages on strip floors and hardwood floors. Excessively wide joints contaminated with dirt and dust in older wood floors, nailed or screwed wood floors are usually not filled with putty, as dry wood putty could partially break loose. After drying it becomes a wood putty mass which is a great filler and has very good adhesion.

Features

- fast drying
- very well sandable
- long time trusted system

Technical Data

Article No.	11085	Application Rate	On newly layed parquet with small joints ca. 100ml/m ² (10m ² /l), (10ml/square foot)
Package Size	12l, 5l, 1l	Application Tool	LOBATOOL stainless trowel
Packing	Box: 1 x 12 l Pallet: 42 x 12 l Box: 4 x 5 l Pallet: 120 x 5 l Box: 12 x 1 l Pallet: 480 x 1 l	Drying Time	Sanding after 30 to 60 minutes, depending on the width of the joint. After 2 h
Solids	11 ± 1%	Thinner	The product is ready-to-use and cannot be diluted!
Storage and Transportation	Store in tightly closed original packages in a cool and dry place. Not sensitive to frost. Storable for at least 24 months - VbF: A1 easily flammalbe – Xi irritant UN-Nr.: 1263 - ADR/RID-GGVS/E: Class 3 F1, Package group III		
GISCODE	G2		

Hazard warnings:

R 11: Highly flammable.
R 36: Irritating to eyes.
R 67: Vapours may cause drowsiness and dizziness.
Xi Irritant
F Highly flammable

LOBADUR® Fugenkittlösung

Information on Use:

- Shake material well
 - Mix LOBADUR® Fugenkittlösung with very fine wood dust from sanding into a soft mass.
 - The finer the sanding dust, the easier you will be able to trowel fill the mass and there will also be a better adhesion in the joints.
 - Before the final cut the complete floor must be smoothed off and on large joints or damages the process must be repeated after drying
 - Peel all remains off of the surface
 - Completely sand off all putty which is left on the surface
 - regard safety regulations
 - Regard climatic conditions*
 - Ventilate working area *
- *)Regard General Information on the strongly solvent based LOBADUR® products

Setup Recommendations for parquet and hardwood floors:

1. Sand with coarse and medium sand paper (grade 36, grade 60)
2. Trowel-fill with putty
3. Drying
4. Final cut (e.g. grade 100 / 120)
5. Surface treatment

Possible Surface Treatment with:

Any waterborne LOBADUR® finish system or any LOBASOL® oil system, without limitation.

The general Information on the use of Strongly Solvent Based LOBADUR® Products are part of this Information and must be noticed.