

LOBASOL[®] Deck & Teak Oil



Product description

Special oil for outdoor use basing on vegetable oils. Due to its good penetration properties the wood will be preserved, but remains vapor-permeable. The woods natural texture and beauty will be accentuated. The friction values according to class R10 of BGR 181 and DIN 51130 will be achieved.

Range of Use

To impregnate outdoor garden furniture, decks and other objects made of teak and other wood species.

Features

- Good penetration behavior
- Basing on vegetable oils
- Increased UV-light resistance
- Excellent weather-resistance
- Easy to apply
- Also suitable for the impregnation of garden furniture

Technical Data

Article No.	10615
Package Size	Transparent 12l, 2,5l, 0,75l Color 2,5l, 0,75l
Packing	Box: 1 x 12l Pallet: 42 x 12l Box: 4 x 2,5l Pallet: 120 x 2,5l Box: 6 x 0,75l Pallet: 432 x 0,75l
Storage and Transportation	Not sensitive to frost, storable for 36 months, no hazardous material according to ADR
Giscode	Ö 60

Store soaked cloth, pads and other tools in closed containers. Sanding dust, cloths, etc. contaminated with oil / wax must be wetted with water, stored in a lockable container or disposed fire-proofely in another way.

Otherwise danger of self-ignition.

Application Rate 100-250ml/m²

The actual consumption rate depends on the type of wood, wood moisture and the weathering condition of the wood. Optimal impregnation/protection effects can only be ensured after achieving complete wood fibre saturation (maximum oil absorption of the wood). In some cases this condition can only be reached after multiple oil applications especially on vertical surfaces (e.g. wall coverings).

Application Tool

Paintbrush, LOBATOOL Oil brush, non-fluffy cloth

Drying Time

Walk on After 12 h

Thinner

Do not dilute. Product is ready to use.

Full declaration

Refined vegetable oils (sunflower oil, wood oil, linseed oil), silicic acid, drying agents (lead-free), antioxidant (free from phenol and oxime), white spirit (de-aromatized, purified)

Color (without color guarantee)



Light Bangkirai



Dark Bangkirai



Douglas fir



Garapa

LOBASOL[®] Deck & Teak Oil

Information on Use:

- Shake material well
- Regard safety regulations
- *) Regard General Information on the use LOBASOL[®] products

Preparation:

For the application an outdoor-temperature at least 10°C is required. Wood that should be impregnated has to be clean and dry. If required remove soilings, moss and old coatings.

Newly installed, widely dense porous woods

are often not capable to absorb sufficient amounts of oil, therefore first of all the pores of the wood have to be opened. This can be caused by outdoor weathering or alternatively by repeated watering (let the wood dry completely after each watering process).

Old heavily soiled and weathered wooden terraces and decks

Cleaning with LOBA[®] Deck & Teak Refresh,

- Apply Deck & Teak refresh undiluted
- Exposure time approx. 10 minutes
- Scrub floor with a hard brush, if necessary apply water
- Rinse dissolved dirt with water
- In case of heavy soilings repeat procedure or extend exposure time of deck & teak oil
- After complete drying apply Deck & Teak Oil

When using a high-pressure cleaner regulate the pressure to ensure the wood surface won't be damaged.

For further details please regard technical information of Deck & Teak Refresh.

Alternatively decks can be brushed automatically, for example with the machine **FG Terrassen-Blitz** and **FG Terrassen-Randy** for edges and small areas.

Application:

1. Apply Deck & Teak Oil in the direction of the woods graining with a non-fluffy cloth.
2. Remove excessive material completely after about 30 minutes penetration time by spreading with a brush or with a non-fluffy cloth.
3. On garden furniture especially on chairs, use absorbent cloths to remove any excessive oil until the surface is almost completely dry.
4. Use LOBATool oil brush on larger areas.
5. If necessary repeat procedure after drying overnight.

Notice:

Before using Deck & Teak Oil Color we recommend to establish a sample area to test the desired color result and appearance of the surface. The different colors can be mixed among each other. In order to achieve a more transparent color Deck & Teak Oil transparent can be added.

The general information on the use of LOBASOL[®] products are part of this information and must be noticed.